

No. of Printed Pages : 4

BFDI-072

CERTIFICATE IN FASHION DESIGN

(CFDE)

Term-End Examination

June, 2023

BFDI-072 : BASICS OF PATTERN MAKING

AND SEWING

Time : 2 Hours

Maximum Marks : 50

Note : Part A—Attempt any *six* questions.

Part B—Attempt any *two* questions.

Part—A

1. Explain various construction lines with respect to the fit of the apparel. 5
2. Discuss the different ways of finishing neck-line in a garment. 5
3. Describe specification sheet with an example. 5

P. T. O.

4. State whether the following statements are True (T) or False (F) : 5
- (a) A garment is a two-dimensional product.
 - (b) Dotted line on a pattern symbolizes the cutting line.
 - (c) Yarns parallel to the selvedge are known as warp yarns.
 - (d) True bias is at 90°.
 - (e) Pin, Blind, Spaced are types of zipp.
5. Differentiate between princess line and style line. 5
6. Enlist the information written on a final pattern. 5
7. Describe the parts which comprise the upright section of a sewing machine. 5
8. What are darts ? Why are they made ? 5

Part—B

9. Explain sewing needle and write about its structure and function in detail. 10

10. What are common sewing problems faced during sewing of a garment ? Explain their causes and remedies in detail. 10
11. What do you understand by special seam situation ? Discuss curved seam and corner seam in detail. 10
12. Fill in the blanks with the correct word : 1 each
- (a) allows the rising and lowering of the needle and moves the thread to the needle.
 - (b) is used as the basics for developing the pattern.
 - (c) is in effect the grading specification for garment pattern capable of being applied for grading.
 - (d) stitch is used as temporary stitch.
 - (e) seam is used for shear fabric.
 - (f) Peter Pan is the name of a
 - (g) Measurement across the back and part of bust is called

- (h) Part of sewing machine that helps the upper thread to move up and down with the needle is called
- (i) A flexible measuring device in taking body measurement is known as
- (j) While mounting the needle, the needle bar should be at the position.