## Diploma in Civil Engineering

## Term-End Examination December, 2010

BCE-034 : ESTIMATING & QUANTITY SURVEYING - I

Time: 2 hours Maximum Marks: 70

Note: Attempt five questions in all. Question no. 1 is compulsory. Assume suitable data, wherever required.

Use of calculator is permitted.

- Write the correct answers from the given alternatives:
  - (a) For the calculation of volumetric quantity of earth work along road alignment, the formula for 'Average cross - sectional area method' is used:
    - (i)  $V = Am \times l$

(ii) 
$$V = \left(\frac{A_1 + A_2}{2}\right) l$$


(iii) 
$$V = \frac{h_1 + h_2}{2} \times l$$

(iv) 
$$V = (A_1 + Am + A_2) l$$

(b)	The long wall and short wall method is			
	suitable for the calculation of items of :			
	(i)	Building works		
	(ii)	Road works		
	(iii)	Canal works		
	(iv)	River training v	vorks	
(c)	Dry Rubble Masonry wall is built by using			
	stones and:			
	(i)	Cement sand m	ortar	1:6
	(ii)	Lime Surkhi mortar 1:3		
	(iii)	Mud mortar		
	(iv)	No mortar		
(d)	For 12 m span, both - side sloped roof the			
	suitable type of roof is:			
	(i)	Couple closed roof		
	(ii)	Collar beam roof		
	(iii)	Queen post roof		
	(iv)	King post roof		
(e)	Acceptable slump for RCC slab is :			
	(i)	1.27 cm to 2.54	cm	
	(ii)	15 cm to 17.50 c	em	
	(iii)	5 cm to 10 cm		
	(iv)	20 cm to 25 cm		
(f)	Unit of measurement of V-grooved pointing			
	on brick work is:			
	``	Per metre	(ii)	Per m <sup>2</sup>
	(iii)	Per m <sup>3</sup>	(iv)	Per kg

(iv) Per kg

- (g) In an estimate which of the following is not part of 'over head charges':
  - (i) Compensatory Insurance for labour
  - (ii) Travelling expenses
  - (iii) Interest and Taxes
  - (iv) Cost of materials
- 2. With the help of the given sketch calculate the following items:  $4\times3^{1/2}=14$ 
  - (i) Quantity of RCC lintels over door and windows assuming bearing on walls 15 cm at each end and lintel thickness 10 cm.
  - (ii) 6 mm thick plaster with cement sand mortar1:3 on RCC roof (flat) ceiling in room.
  - (iii) Cement concrete flooring in room including door sill.
  - (iv) Quantity required to be deducted from brick wall for door and windows openings.



- 3. Calculate the quantity of earth work in filling for a 70 m long railway track using 'Average Cross -Sectional Area method' with the help of given data:
  1x14=14
  - Cross-sectional area at one end for earth filling  $(A_1) = 30 \text{ m}^2$
  - Cross sectional area at other end for earth filling  $(A_2) = 20 \text{ m}^2$ .
- 4. Prepare the analysis of rates of any two of the following:

  2x7=14
  - (a) Cement concrete in foundations and under floors with 4 cm gauge brick ballast and fine sand in the proportion of 1 : 5 : 10 (cement : sand : brick ballast)
  - (b) First class brick work in lime and Surkhi mortar 1 : 2 in foundation and Plinth
  - (c) Second class brick work in mud mortar in super-structure.
  - (d) 12 mm thick, cement and sand mortar 1: 6, plastering on brick work - including base preparation etc.
- 5. Differentiate between any four of the following:
  - (a) Plain cement concrete and reinforced cement concrete. 4x3½=14
  - (b) Segmental Arch and Semi-circular Arch.
  - (c) Surface excavation and excavation for foundation trench of wall footings.

- (d) Random Rubble Masonry and Dry Rubble Masonry
- (e) Lump-sum contract and Percentage contract
- (f) Cement Plastering and Painting
- **6.** Write specifications for *any two* of the following:
  - (a) First class brick work in cement sand mortar
    1:4
    2x7=14
  - (b) Ashlar Masonry with cement sand mortar 1:4.
  - (c) King Post Truss with steel sections
  - (d) Cement Plastering on brick work
- 7. Write short notes on any four of the following:
  - (a) Maintenance and repair works  $4x3\frac{1}{2}=14$
  - (b) Estimation of over head charges
  - (c) Mixing of cement concrete
  - (d) Sloped roofs
  - (e) Mid-sectional Area Method of earth work along road alignment.
  - (f) Arch work in stone masonry.